

89FEL

Freestanding Tyre Inflator with Large Display

Based on the 89FEP freestanding unit, the 89FEL offers a significantly larger and brighter LED display.

On a petroleum forecourt, the LED display draws attention with its distinctive glow and provides a point of difference from typical freestanding inflators.

The lens colour and faceplate can be customised to suit your corporate brand and local language.

Contact Airtec Corporation for further technical information.




89FEL

Product Features

- Fast and accurate digital inflation up to 145 psi / 10 bar
- Bright, superior, long-lasting LED display
- 57mm digits visible from a long distance (as compared to the standard 25mm digits)
- Displays up to two units of measurement or indication of inflation/deflation cycle
- Sleek design with small footprint
- Piezo control switches as standard
- Supplied with 10m hose kit
- Corporate and customised designs available

Technical Specifications

Construction	: Diecast aluminium enclosure (IP46)
Dimension	: 320 W x 1400 H x 320 D mm
Power requirements	: 220V-240VAC (optional 100~120VAC)
Units of measurement	: psi / kPa / bar / kg/cm ²
Operating range	: 5-145 psi / 35-1000 kPa / 0.3-10.0 bar / 0.4-10.2 kg/cm ²
Reading precision	: 1 psi / 5 kPa / 0.10 bar / 0.1 kg/cm ²
Accuracy	: +/- 0.5% FS
Operating temperature	: 0°C to +60°C [32°F to 140°F] (without heater) : -20°C to +60°C [-4°F to 140°F] (with heater)



Colour choices for lens

Optional Accessories



47.0020
Cabinet
Heater (kit)



94.0100
Standard
Tap (kit)



94.0101
Push Button
Tap (kit)



94.0612
Filter
Regulator