

89FRP / FRD

Single / Dual Display Freestanding Digital Tyre Inflator

The 89FRP/FRD model now comes with the choice of using our **new slow retract hose reels**, standard retractable hose reels or just the 10m dual braided hose kit.

With its user-friendly controls, it is available in single and dual display version. The dual display indicates target pressure and tyre pressure separately during the inflation cycle.

Its futuristic shape and ergonomic design blends with any corporate image. With the optional in-built compressor, air is supplied directly from the pump. As no pressure vessel is needed, inspection and certification costs are therefore eliminated.

This model is the ultimate self-contained tyre inflation solution designed for the petroleum forecourts.

Please contact Airtec Corporation for further technical information.



89FRP



89FRD

Product Features

Fast and accurate digital inflation up to 145 psi / 10 bar (without in-built compressor)

Retractable reels are supplied with 7m steel braided hose assembly

Piezo control switches as standard

Corporate and customised designs available

Innovative Award Winning Design

Technical Specifications

Construction	: Diecast aluminium enclosure (IP44)
Dimension	: 410 W x 1400 H x 450 D mm
Power requirements	: 220V-240VAC (optional 100~120VAC)
Units of measurement	: psi / kPa / bar / kg/cm ²
Operating range	: 5-145 psi / 35-1000 kPa / 0.3-10.0 bar / 0.4-10.2 kg/cm ² (without in-built compressor) : 5-116 psi / 35-800 kPa / 0.3-8.0 bar / 0.4-8.1 kg/cm ² (with in-built compressor)
Reading precision	: 1 psi / 5 kPa / 0.10 bar / 0.1 kg/cm ²
Accuracy	: +/- 0.5% FS
Operating temperature	: 0°C to +60°C [32°F to 140°F] (without heater) : -20°C to +60°C [-4°F to 140°F] (with heater)

Optional Accessories



31.0210
Cast Compressor
230V 50Hz



63.0520
Reel Assembly
(less hose)



63.0521
Water Reel
Assembly



47.0022
Cabinet
Heater (kit)



94.0612
Filter
Regulator