

89FRP

Single Display Freestanding Digital Tyre Inflator (with bicycle inflation)

Introducing the new 89FRP inflator model that comes with the choice of dual inflation mode - vehicle and bicycle tyres.

The inflator is very simple to operate. Users can select the switch on the user-friendly control panel, to start the desired inflation for a safe, quick and accurate inflation.

The bicycle inflation hose is equipped with a twin head chuck dedicated for bicycle tyres with Presta/Dunlop or Schrader valves.

Finally an inflator that cyclist can safely use to inflate their tyres.

Please contact Airtec Corporation for further technical information.



89FRP

Product Features

- Fast and accurate digital inflation up to 145 psi / 10 bar (with external air supply)
- Piezo control switches as standard
- Corporate and customised designs available
- Innovative Award Winning Design

Technical Specifications

Construction	: Diecast aluminium enclosure (IP44)
Dimension	: 410 W x 1400 H x 450 D mm
Power requirements	: 220V-240VAC (optional 100~120VAC)
Units of measurement	: psi / kPa / bar / kg/cm ²
Operating range	: 5-145 psi / 35-1000 kPa / 0.3-10.0 bar / 0.4-10.2 kg/cm ² (with external air supply) : 5-116 psi / 35-800 kPa / 0.3-8.0 bar / 0.4-8.1 kg/cm ² (with in-built compressor)
Reading precision	: 1 psi / 5 kPa / 0.10 bar / 0.1 kg/cm ²
Accuracy	: +/- 0.5% FS
Operating temperature	: 0°C to +60°C [32°F to 140°F] (without heater) : -20°C to +60°C [-4°F to 140°F] (with heater)

Optional Accessories



31.0210
Compressor
230V 50Hz



91.0202
Twin Head
Chuck



63.0521
Water Reel
Assembly



47.0022
Cabinet
Heater (kit)



94.0612
Filter
Regulator