

89ML Series

Digital Tyre Inflator with Large Display

Based on the footprint of the benchmark Airtec inflators in a moulded enclosure (89MFD and 89MDA), the 89ML Series offers a significantly larger, brighter and more attractive front display to the standard LCD. This long-lasting LED display is well suited for truck workshops and inflation of large vehicles where operators traditionally experience difficulties in viewing the inflator display.

The 89MLF is designed for panel or recess mounting (suited for OEM applications).

The display lens is available in a range of colours; along with the front panel design can also be customised to suit your corporate image or language.



89MLF

Product Features

Bright, superior and long-lasting LED display

57mm digits visible from a long distance (as compared to the standard 25mm digits)

Displays up to two units of measurement or indicator of inflation/deflation cycle

Panel mount version (89MLF)

Vandal resistant piezo switches

Technical Specifications

| | |
|-----------------------|---|
| Construction | : High impact Polycarbonate Enclosure IP66 |
| Dimension | : 220W x 260H x 100D mm |
| Power requirements | : 220-240V AC (optional 12V DC or 100~120V AC) |
| Units of measurement | : psi / kPa / bar / kg/cm ² (Up to two max) |
| Operating range | : 5-145 psi / 35-1000kPa / 0.3-10.0 bar / 0.4-10.2 kg/cm ² |
| Accuracy | : +/- 0.5% FS |
| Operating temperature | : 0°C to +60°C [32°F to 140°F] (without heater) : -20°C to +60°C [-4°F to 140°F] (with heater) |

Optional Accessories



91.0213
Clip-On
Hose Chuck



61.0028
10m Hose Kit



94.0601
Filter Regulator