

89TR6

Mobile Inflation System - Nitrogen

The 89TR6 offers a portable standalone solution for Nitrogen filling of tyres. The rugged mobile design system enables ease of use in motor racing pits, workshops, fleet control, tyre stores, lube shops and auto dealerships.

Using an industry standard bottle as a source or direct from Nitrogen generator, it can inflate up to 6 tyres simultaneously. The battery life is extended by an automatic power off function. In typical use, the unit will only have to be recharged every few days as high capacity NiMH batteries are used.

The 89TR6 is supplied with 4x8m hoses with clip-on closed chuck. The integrated accessory box provides storage compartments for chucks and other components like valve cores and caps.

Our specially developed Nitrogen filling and purging software makes Nitrogen conversion faster and easier.

Please contact Airtec Corporation for further technical information.



89TR6

Product Features

- Automatic Purging Program (N2P)
- Adjustable Over Pressure Settings (OPS)
- Inflate up to 6 tyres simultaneously
- Power Saving Auto Power Off
- Rugged and Durable Design
- Weatherproof
- Suits Standard Nitrogen Bottle / Direct Nitrogen Supply from Generator

Technical Specifications

Construction	: Galvanised Steel Frame, powder coated
Power requirements	: 12V DC External Battery included 100-240V AC 50/60Hz Smart Charger included
Units of measurement	: psi / kPa / bar / kg/cm ²
Operating range	: 5-145psi / 35-1000kPa / 0.3-10.0bar / 0.4-10.2kg/cm ²
Accuracy	: +/- 0.5% FS
Operating temperature	: 0°C to + 60°C [32°F to 140°F] without heater

Accessories Included :

