

# FEL

## Freestanding Tyre Inflator with Large Display

Based on the FEP freestanding unit, the FEL offers a significantly larger, brighter and more attractive front display to the standard LCD.

On a petroleum forecourt, the attractive display draws attention with its distinctive glow and provides a point of difference from typical freestanding inflators.

The lens colour and faceplate can be customised to suit your corporate brand and local language.

Contact Airtec Corporation for further technical information.



89FEL

### Product Features

- Fast and accurate digital inflation up to 145 psi / 10 bar
- Bright, superior, long-life LED display
- 57mm digits visible from a long distance (as compared to the standard 25mm digits)
- Displays up to two units of measurement or indication of inflation/deflation cycle
- Sleek design with small footprint
- Piezo control switches as standard
- Supplied with 10m hose kit
- Corporate and customised designs available

### Technical Specifications

Construction	: Diecast aluminium enclosure (IP46)
Dimension	: 320 W x 1400 H x 320 D mm
Power requirements	: 220V-240VAC (optional 100~120VAC)
Units of measurement	: psi / kPa / bar / kg/cm <sup>2</sup>
Operating range	: 5-145 psi / 35-1000 kPa / 0.3-10.0 bar / 0.4-10.2 kg/cm <sup>2</sup>
Reading precision	: 1 psi / 5 kPa / 0.10 bar / 0.1 kg/cm <sup>2</sup>
Accuracy	: Up to ± 0.5% FS
Operating temperature	: 0°C to +60°C [32°F to 140°F] (without heater) : -20°C to +60°C [-4°F to 140°F] (with heater)



Colour choices for lens

### Optional Accessories



47.0020  
Cabinet  
Heater (kit)



94.0100  
Standard  
Tap (kit)



94.0101  
Push Button  
Tap (kit)



94.0612  
Filter  
Regulator