

FEP / FED

Single / Dual Freestanding Digital Tyre Inflator (square profile)

The FEP and FED models are specially designed for the petroleum forecourts enhancing site image and providing safe, accurate and reliable tyre inflation for customers.

It is available in single and dual display version. The dual display indicates target pressure and tyre pressure separately during the inflation cycle.

Our extensive range of high-grade powder coat colours completes the ultimate low maintenance solution for service and gas station tyre inflation systems.

Please contact Airtec Corporation for further technical information.



Product Features

- Fast and accurate digital inflation up to 145 psi / 10 bar
- Sleek design with small footprint
- Piezo control switches as standard
- Supplied with 10m hose kit
- Corporate and customised designs available

Technical Specifications

Construction	: Diecast aluminium enclosure (IP46)
Dimension	: 320 W x 1400 H x 320 D mm
Power requirements	: 220V-240VAC (optional 100~120VAC)
Units of measurement	: psi / kPa / bar / kg/cm ²
Operating range	: 5-145 psi / 35-1000 kPa / 0.3-10.0 bar / 0.4-10.2 kg/cm ²
Reading precision	: 1 psi / 5 kPa / 0.10 bar / 0.1 kg/cm ²
Accuracy	: Up to ± 0.5% FS
Operating temperature	: 0°C to +60°C [32°F to 140°F] (without heater) : -20°C to +60°C [-4°F to 140°F] (with heater)

Optional Accessories



47.0020
Cabinet
Heater (kit)



94.0100
Standard
Tap (kit)



94.0101
Push Button
Tap (kit)



94.0612
Filter
Regulator