

## MDA

### General Purpose Digital Tyre Inflator

The MDA model is designed for use in vehicle workshops and service centres.

Suitable for all sizes of pneumatic tyres including trolleys, bicycles, cars and trucks.

Contact Airtec Corporation for further technical information.



89MDA

#### Product Features

- Safe, accurate and easy to use
- Easy installation
- Economically priced
- Impact resistant enclosure
- Supplied with 10m hose kit

#### Technical Specifications

Construction	: High impact polycarbonate enclosure (IP66)
Dimension	: 220W x 220H x 100D mm
Power requirements	: 220V-240VAC (optional 12VDC or 100~120VAC)
Units of measurement	: psi / kPa / bar / kg/cm <sup>2</sup>
Operating range	: 5-145 psi, 35-1000 kPa, 0.3-10.0 bar, 0.4-10.2 kg/cm <sup>2</sup>
Reading precision	: 1 psi / 5 kPa / 0.10 bar / 0.1 kg/cm <sup>2</sup>
Accuracy	: Up to $\pm 0.5\%$ FS
Operating temperature	: 0°C to +60°C [32°F to 140°F] (without heater) : -20°C to +60°C [-4°F to 140°F] (with heater)

#### Optional Accessories



91.0213  
Clip-on  
Hose Chuck, Open