

## ML Series

### Digital Tyre Inflator with Large Display

Based on the footprint of the benchmark Airtec inflators in a moulded enclosure (MFD and MDA), the ML Series offers a significantly larger, brighter and more attractive front display to the standard LCD. This long-life LCD display is well suited to truck workshops and inflation of large vehicles where operators traditionally experience difficulty in viewing the inflator display.

The MLF is designed for panel or recess mounting (suited for OEM applications).

The display lens is available in a range of colours; along with the front panel design can also be customised to suit your corporate image or language.



89MLF

#### Product Features

Bright, superior, long-life LCD display

57mm digits visible from a long distance (as compared to the standard 25mm digits)

Displays up to two units of measurement or indicator of inflation/deflation cycle

Panel mount version (MLF)

Vandal resistant stainless steel mechanical switches

#### Technical Specifications

Construction : High impact Polycarbonate Enclosure IP66

Dimension : 220W x 260H x 100D mm

Power requirements : 220-240V AC (optional 12V DC or 100~120V AC)

Units of measurement : psi / kPa / bar / kg/cm<sup>2</sup> (Up to two max)

Operating range : 5-145 psi / 35-1000kPa / 0.3-10.0 bar / 0.4-10.2 kg/cm<sup>2</sup>

Accuracy : Up to ± 0.5% FS

Operating temperature : 0°C to +60°C [32°F to 140°F] (without heater)

: -20°C to +60°C [-4°F to 140°F] (with heater)

#### Optional Accessories



91.0213  
Clip-On  
Hose Chuck



61.0028  
10m Hose Kit



94.0601  
Filter Regulator