

XDX / XDZ

Over Inflator

The XDX/XDZ models are specifically designed for the tyre fitting industry.

The desired over-pressure value can be set in the top display and the final pressure in the lower display.

The automatic process will inflate to the over-pressure setting, then deflate to the final pressure setting.

The XDZ is a high flow model and can be used for inflating large or multiple tyres.

Contact Airtec Corporation for further technical information.



89XDX

Product Features

- Pressure Hold Time
- Purge function for Nitrogen Inflation
- Emergency Stop Control
- Large Backlit LCD
- Supplied with 2m hose kit (applicable to 89XDX)
- Customisable preset pressure switches

Technical Specifications

Construction	: Diecast aluminium wall/surface mount enclosure (IP66)
Dimension	: 269W x 285H x 106D mm
Power requirements	: 220V-240VAC (optional 12VDC or 100~120VAC)
Units of measurement	: psi / kPa / bar / kg/cm ²
Operating range	: 5-145 psi, 35-1000 kPa, 0.3-10.0 bar, 0.4-10.2 kg/cm ²
Reading precision	: 1 psi / 5 kPa / 0.10 bar / 0.1 kg/cm ²
Accuracy	: Up to ± 0.5% FS
Operating temperature	: 0°C to +60°C [32°F to 140°F] (without heater) : -20°C to +60°C [-4°F to 140°F] (with heater)



89XDZ

Optional Accessories



93.2802
4 way
Manifold Kit



94.0600
Air filter /
Auto-drain / Regulator



97.5058
Core
Retracting Tool



45.5652
Remote
Emergency Stop